

Xtra-SHIFT 8HP

Xtra-SHIFT 8HP is a Synthetic Automatic Transmission Fluid with the following properties:

Excellent quality properties

High load capacity, outstanding wear minimisation

Exceptional friction coefficient consistency

No foaming

Very low evaporation loss

Excellent gear shifting properties at low temperatures

Adapted friction coefficient properties for sports-style gear shifting

Outstanding oxidation and thermal stability

No adverse effect on standard sealing materials

Use instructions:

Specially designed for modern ZF 6-/8-/ and 9-speed automatic transmissions in high-powered vehicles Not for use in DCT/DSG- (Double Clutch) or CVT- (Continuously-Automatic) transmissions suitable.

Observe manufacturer instructions!

Colour: slightly green

Specification

Recommended application

BMW 83222289720 VW G 060 162 Chrysler 68157995AA Fiat 9.55550-AV5 Jaguar 02JDE26444 Land Rover LR023288 ZF 5671 090 312





Technical data	Unit	Test according	Xtra-SHIFT 8HP
density at 15°C	Kg/m³	DIN EN ISO 12185	845
Flammable COC	°C	DIN ISO 2592	210
Pourpoint	°C	DIN ISO 3016	-48
Viscosity 40°C	mm²/s	DIN 51562-1	28,1
Viscosity 100°C	mm²/s	DIN 51562-1	5,94
VI		DIN ISO 2909	164

The expiration date is 3 years after production date under the permission that the product is stored in a dark, dry and cool place.

The given data are typical data. Please observe instructions.