

## **FD ECO SAE 5W-20**

FD ECO 5W-20 is a HC-synthetic high-performance, low-viscosity engine oil of latest technology especially for modern Ford EcoBoost engines.

Excellent cold-start behaviour ensures optimum lubrication reliability in the cold-running phase. The special additives improve the protection of the catalytic converter. Guarantees highest engine cleanliness and best wear protection. Exceptional product stability enables extended oil change intervals.

FD ECO 5W-20 guarantees a fuel saving potential of up to 3% and contributes to environmental protection by reducing CO2 emissions.

## Application notes:

FD ECO 5W-20 was developed especially for the latest Ford EcoBoost engines.

Observe manufacturers instructions.

## **Specification**

ACEA C5 API SN (RC) / CF ILSAC GF-5

## **Recommended application**

Chrysler MS-6395
Fiat 9.55535-CR1
Ford WSS-M2C948-A/B
Ford WSS-M2C912-A
Ford WSS-M2C913-A/B/C
Ford WSS-M2C925-B
Jaguar Land Rover STJLR.03.5004





Technical data	Unit	Test according	FD ECO SAE 5W-20
density at 15°C	Kg/m³	DIN EN ISO 12185	845,8
Flammable COC	°C	DIN ISO 2592	226
Pourpoint	°C	DIN ISO 3016	-42
Viscosity 40°C	mm²/s	DIN 51562-1	44,75
Viscosity 100°C	mm²/s	DIN 51562-1	8,27
VI		DIN ISO 2909	162

The expiration date is 3 years after production date under the permission that the product is stored in a dark, dry and cool place.

The given data are typical data. Please observe instructions.