

# Technical Data Sheet



# **Typical Inspection Data:**

Density @ 20 °C	0.850 g/cm <sup>3</sup>
Viscosity @ 100 °C	11.7 cSt
Viscosity @ 40 °C	68 cSt
Viscosity Index	170
Viscosity CCS @ -30 °C	5700 cP
T.B.N.	8.6 mg KOH/g
Sulphated Ash Mass	0.8%
Zinc	0.10%
Calcium	0.17%
Phosphorus	0.09%
Colour	Brown
Flash Point	230 °C
Pour Point	-39 °C

# Prolife 5W-30

**Fully Synthetic** 

### **Official Approvals:**

Approved under VW standard 504 00 and VW standard 507 00

**Recommended by Comma for applications requiring:** 

MB 229.51; BMW LL-04; PORSCHE C30 ACEA C3

#### **Product Features:**

- Fully synthetic, high performance 5W-30 low SAPS oil for modern VW-Audi group petrol and diesel vehicles including those operating under long life service regimes. Also protects exhaust after-treatment units.
- Do not mix this oil with other types of oil, as the requirement for exhaust after-treatment protection will no longer be guaranteed.
- To ensure correct oil selection check Comma's latest application guide in store or online at CommaOil.com.

# Handling:

- Avoid extremes of temperature.
- Product in cardboard cartons must be stored under cover and away from damp conditions.
- Barrels should be stored under cover if possible.
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs.

# Shelf Life:

- 5 years from date of manufacture.
- Manufacture date can be identified from a five figure code printed on the bottle. The first three figures indicate the consecutive day of the year, the last two figures the year.

25-05-2017

#### Comma Oil & Chemicals Ltd.

Dering Way, Gravesend, Kent DA12 2QX, England. Tel: +44 (0)1474 564311, Fax: +44 (0)1474 333000 Email: sales@commaoil.com www.CommaOil.com