

EVOLUTION GEAR SAE 75W-90 GL4

EVOLUTION GEAR SAE 75W-90 GL4 is a semi-synthetic low-viscosity gear oil for manual transmissions and normally-loaded axle drives.

EVOLUTION GEAR SAE 75W-90 GL4 possesses various advantages compared to conventional gear oils:

Excellent cold properties

Excellent thermal stability

Very high viscosity index

Very high shear stability

Avoidance of cold scratches and effective noise damping

Excellent corrosion protection

Reduction of fuel consumption

Extension of oil change intervals

Less abrasion and consequently extended gear life

Use instructions:

EVOLUTION GEAR SAE 75W-90 GL4 is used for the lubrication of normal loaded axle transmissions with low axle offset as well as in synchronized and non-synchronized manual transmissions and in steering and transfer cases of motor vehicles and work machinery.

Specification

API GL-4

Recommended application

MAN 341 E-1, Z-2 MB 235.1 ZF TE-ML 02B, 16A,17A, 19C

Technical data	Unit	Test according	EVOLUTION GEAR SAE 75W-90 GL4
density at 15°C	Kg/m³	DIN EN ISO 12185	875
Flammable COC	°C	DIN ISO 2592	234
Pourpoint	°C	DIN ISO 3016	-45
Viscosity 40°C	mm²/s	DIN 51562-1	82,30
Viscosity 100°C	mm²/s	DIN 51562-1	14,47
VI		DIN ISO 2909	184

The expiration date is 3 years after production date under the permission that the product is stored in a dark, dry and cool place.

The given data are typical data. Please observe instructions.



PROFI-CAR MADE IN GERMANY



