

## ECO-DRIVE FE+ SAE OW-20

ECO-DRIVE FE+ SAE 0W-20 is all thermal and mechanical burdens grown in modern, on fuel economy designed car engines can occur. A high cleaning and dirt-bearing power ensures the highest engine cleanliness and best wear protection.

ECO-DRIVE FE+ SAE 0W-20 ensures a fuel Saving potential and contributes to the protection of the environment reduction of CO<sup>2</sup> emissions at.

ECO-DRIVE FE+ SAE 0W-20 is a year-round low-viscosity engine oil for passenger car engines, for the fuel economy (FE) prescribed or are released.

ECO-DRIVE FE+ SAE 0W-20 is fully compatible with the latest diesel particulate filters (DPF) and with the catalytic converters of petrol engines.

## **Specification**

ACEA C5
API SN, SN Plus
API SN Plus Resource Conserving
ILSAC GF-5

## **Recommended application**

BMW Longlife-17 FE+ GM DexosD MB 229.71 Opel/ Vauxhall OV0401547 Volvo VCC RBS0-2AE

Technical data	Unit	Test according	ECO-DRIVE FE+ SAE OW-20
density at 15°C	Kg/m³	DIN EN ISO 12185	844
Flammable COC	°C	DIN ISO 2592	230
Pourpoint	°C	DIN ISO 3016	-49
Viscosity 40°C	mm²/s	DIN 51562-1	40,9
Viscosity 100°C	mm²/s	DIN 51562-1	8,2
VI		DIN ISO 2909	179
TBN	mgKOH/g	DIN ISO 3771	7,4

The expiration date is 3 years after production date under the permission that the product is stored in a dark, dry and cool place.

The given data are typical data. Please observe instructions.

