



1 L | 1410122-010 1.5 L | 1410122-150 5 L | 1410122-005 20 L | 1410122-020 20 L | 1410122-B20 60 L | 1410122-060 208 L | 1410122-208 1000 L | 1410122-700

# RAVENOL HJC CONCENTRATE PROTECT FL22

CategoryRadiator antifreeze

Item number1410122

**Recommendation** 08CLAG010S0 Honda E Coolant, Ford VC-10-A2, Hyundai 00232-19010, Hyundai 07100-00200, Hyundai 07100-00400, Hyundai Long Life Coolant, Mazda 000077508E20, Mazda C100CL005A4X, Mazda C122CL005A4X, Mazda FL22 Coolant, Nissan Anti-freeze Coolant (L250), Nissan KE90299934, Nissan KE90299944, Subaru Coolant 16218, Suzuki Longlife Coolant, WSS-M97B55

**Application** Passenger car

### **RAVENOL HJC Hybrid Japanese Coolant**

**Concentrate** is an ethylene-glycol based, proven coolant without, amines and silicates. The product is formulated as a long-term coolant based on a proven inhibitor development.

It is no longer just the anti-freeze effect (which automatically exists in an ethylene-glycol based product) which is critical for the quality of a coolant, but also the rust protection.

Therefore automakers subject coolants to long corrosion and cavitation tests.

**RAVENOL HJC Hybrid Japanese Coolant Concentrate** protects the cooling system from corrosion, frost, and in the summer from overheating.

# **Application Note**

#### **RAVENOL HJC Hybrid Japanese Coolant**

**Concentrate** with frost and rust protection. Use according to the mixing chart. Follow manufacturer's recommendations.

Even in summer coolant must contain enough antifreeze to ensure good corrosion and overheating protection.

Instructions: Clean cooling system, check for leaks, flush.

MIX **RAVENOL HJC Hybrid Japanese Coolant Concentrate** with fresh water (per mixing chart) and add. Allow engine and heater to warm up, add coolant to fill level.

### **Characteristics**

- Excellent for light metal engines
- Good reserve alkalinity

- High-quality corrosion additives for optimal corrosion protection
- Elastomer compatible with elastomers used in automotive radiators

## **Technical Product Data**

Density at 20 °C	1132,0	kg/m³	EN ISO 12185
Colour	grün		VISUELL
Flashpoint	>110	°C	DIN 51758
Boiling point	>150	°C	ASTM D1121
pH - value at 20 °C (50 Vol %)	7,0 - 8,5		ASTM D1287
Reserve alkalinity	min. 15	ml0,1nHCl	ASTM D1120
Water content	<5	Gew. %	ASTM D1123
Freezing point (50 % solution)	-37	°C	ASTM D1177

20.01.2022