

Technical Data Sheet



Typical Inspection Data: Density @ 20°C 0.850 g/cm³ Viscosity @ 100°C 11.9 cSt Viscosity @ 40°C 70 cSt Viscosity Index 165 Viscosity CCS @ -30°C 5900 cP T.B.N. 7.8 mg KOH/g Sulphated Ash Mass 0.8% Zinc 0.10% Calcium 0.18% 0.08% **Phosphorus** Colour Brown Flash Point 210°C **Pour Point** -36°C

X-Flow Type Z 5W-30

Fully Synthetic

Recommended by Comma for applications requiring:

MB 229.31; MB 229.51; BMW LL-04; dexos 2; VW 502 00, VW 505 00 ACEA C3 API SL CF

Direction of use:

- Fully synthetic 5W-30 low SAPS oil for modern petrol and diesel vehicles including those fitted with exhaust aftertreatment units that require an ACEA C3 grade.
- To ensure correct oil selection check Comma's latest application guide in store or online at CommaOil.com.

Handling:

- Avoid extremes of temperature.
- Product in cardboard cartons must be stored under cover and away from damp conditions.
- Barrels should be stored under cover if possible.
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs.

Shelf Life:

- 5 years from date of manufacture.
- Manufacture date can be identified from an eight digit code printed on the bottle. YYYY.MM.DD.

UPDATED: 03.05.2019