

Technical Data Sheet



Typical Inspection Data: 0.848 g/cm³ Density @ 20 °C Viscosity @ 100 °C 9.9 cSt Viscosity @ 40 °C 55 cSt Viscosity Index 166 Viscosity CCS @ -30 °C 4000 cP T.B.N. 10.0 mg KOH/g Sulphated Ash Mass 1.1% Zinc 0.12% Calcium 0.26% **Phosphorus** 0.10% Colour Brown Flash Point 230 °C **Pour Point** -36 °C

Xtech 5W-30

Fully Synthetic

Official Approvals:

Acknowledged by Ford to meet the requirements of WSS-M2C913-D

Recommended by Comma for applications requiring:

FORD WSS-M2C913-C, WSS-M2C913-B, WSS-M2C913-A; Jaguar Land Rover STJLR 03.5003; ACEA A5/B5; API SL CF

Product Features:

- Fully synthetic, high performance 5W-30 oil, for Ford DuraTec, DuraTorq and Zetec Vehicles, offering the fuel economy benefits of an ACEA A5/B5 oil.
- To ensure correct oil selection check Comma's latest application guide in store or online at CommaOil.com.

Handling:

- Avoid extremes of temperature.
- Product in cardboard cartons must be stored under cover and away from damp conditions.
- Barrels should be stored under cover if possible.
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs.

Shelf Life:

- 5 years from date of manufacture.
- Manufacture date can be identified from an eight digit code printed on the bottle. YYYY.MM.DD.

12-09-2017