

## **WAVE POWER SPECIAL FEB 5W-20**

**Fully Synthetic Passenger Car Engine oil** 

**WAVE POWER SPECIAL FEB 5W-20** is a high-quality fuel saving engine oil based on 100% synthetic technology specially designed for the latest Ford Ecoboost gasoline engines. **WAVE POWER SPECIAL FEB 5W-20** is also suited for engines where API: SN, ACEA C5 or former ACEA A1/B1 is recommended.

**WAVE POWER SPECIAL FEB 5W-20** is based on high performance synthetic oil in combination with a specially selected additive technology to ensure the following properties.

- Excellent thermo- and oxidation stability.
- Very high detergency and dispersion.
- Very good low temperature properties.
- Protection to wear by cold start.
- Excellent resistance against foaming, corrosion and wear.
- High dispersancy and detergency level.
- High and stable viscosity index.
- Low Fuel Consumption.

**WAVE POWER SPECIAL FEB 5W-20** meets the following performance criteria:

API SN ACEA C5 Ford WSS M2C-948B STJLR.03.5004

**Typical Analysis** 

| Properties                  | Unit                            | Method     | Typical Value |
|-----------------------------|---------------------------------|------------|---------------|
|                             |                                 |            |               |
| SAE Grade                   |                                 | SAE J300   | 5W-20         |
| Density @15°C               | kg/m³                           | ASTM 4052  | 852           |
| Kinematic Viscosity @ 40°C  | mm <sup>2</sup> /s              | ASTM D7042 | 42.6          |
| Kinematic Viscosity @ 100°C | mm²/s                           | ASTM D7042 | 7.9           |
| Viscosity Index             |                                 | ASTM D2270 | 159           |
| Viscosity CCS @ -30°C       | сР                              | ASTM D5293 | 6600          |
| Flash Point COC             | °C                              | ASTM D92   | >201          |
| Pour Point                  | °C                              | ASTM D7346 | -42           |
| Total Base Number           | mgKOH/g                         | ASTM D2896 | 7.4           |
| Sulphated Ash               | %Wt                             | ASTM D874  | 0.78          |
| Date Issued: 17-6-2021      | Supersedes: 22-03-2019 Revision |            | on Nr.: 02    |















