



Typical Inspection Data:

| | |
|------------------------|-------------------------|
| Density @ 20 °C | 0.847 g/cm ³ |
| Viscosity @ 100 °C | 9.8 cSt |
| Viscosity @ 40 °C | 53 cSt |
| Viscosity Index | 170 |
| Viscosity CCS @ -30 °C | 3900 cP |
| T.B.N. | 9.5 mg KOH/g |
| Sulphated Ash Mass | 1.1% |
| Zinc | 0.11% |
| Calcium | 0.26% |
| Phosphorus | 0.11% |
| Colour | Brown |
| Flash Point | 230 °C |
| Pour Point | -36 °C |

X-Flow Type F PLUS 5W-30

Fully Synthetic

Recommended by Comma for applications requiring:

FORD WSS-M2C913-A, WSS-M2C913-B, WSS-M2C913-C
ACEA A1/B1; ACEA A5/B5
API SL CF

Product Features:

- Fully synthetic 5W-30 oil for Ford petrol and diesel engines including Zetec and pre 2009 DuraTec and DuraTorq engines.
- To ensure correct oil selection check Comma's latest application guide in store or online at CommaOil.com.

Handling:

- Avoid extremes of temperature.
- Product in cardboard cartons must be stored under cover and away from damp conditions.
- Barrels should be stored under cover if possible.
- If barrels must be stored outside then lay them on their side to prevent water collecting around the bungs.

Shelf Life:

- 5 years from date of manufacture.
- Manufacture date can be identified from a five figure code printed on the bottle. The first three figures indicate the consecutive day of the year, the last two figures the year.

18-01-17