

WAVE POWER EXCELLENCE 5W-30

Full Synthetic Passenger Car Engine oil

WAVE POWER EXCELLENCE 5W-30 is an universal high performance fuel saving oil based on 100% synthetic technology for use in gasoline- and diesel engines of passenger car and light vans with or without turbocharger. This product is unsuitable for diesel engines equipped with a Diesel Particulate Filter (DPF).

WAVE POWER EXCELLENCE 5W-30 is formulated with high quality synthetic base stocks in combination with an unique additive technology to achieve the following performance:

- Very good low temperature properties.
- Protection to wear by cold start.
- Very high thermal and oxidation stability.
- Excellent resistance against foaming, corrosion and wear.
- High dispersancy and detergency level.
- High Viscosity Index.

WAVE POWER EXCELLENCE 5W-30 meets the following performance criteria:

API SP* ACEA A3/B4 MB 226.5 MB 229.3 MB 229.5 Renault 0700/0710 VW 502.00/505.00 GM-LL-025-A

GM-LL-025-B

*exceeds API SP performance, but does not meet phosphorus limit

Typical Analysis

Properties	Unit	Method	Typical Value
SAE Grade		SAE J300	5W-30
Density @15°C	kg/m³	ASTM 4052	850
Kinematic Viscosity @ 40°C	mm²/s	ASTM D7042	69.4
Kinematic Viscosity @ 100°C	mm²/s	ASTM D7042	11.8
Viscosity Index		ASTM D2270	166
Viscosity CCS @ -30°C	сР	ASTM D5293	5800
Flash Point COC	°C	ASTM D92	>200
Pour Point	°C	ASTM D7346	-36
Total Base Number	mgKOH/g	ASTM D2896	11.0
Sulphated Ash	%Wt	ASTM D874	1.3
Date Issued: 27-01-2023	Supersedes: 17-06-2	2021 Revision	on Nr.: 03















