

## STREAM POWER OTB 4T

### 4-Stroke Outboard Engine Oil

**STREAM POWER OTB 4T** is a premium 4-stroke engine oil specially designed for the most modern high output gasoline power, water cooled outboard / inboard and personal watercraft engines. It is specially developed to exceed the performance requirements of National Marine Manufacturers Association's specification NMMA FC-W® (Four Cycle-Water specification).

**STREAM POWER OTB 4T** is based on high-quality hydro processed base oils in combination with a special selected additive package to obtain the following properties:

- Exceptional shear stability.
- Advanced rust inhibitors guard against rust & corrosion even in marine salt water environment.
- Good low temperature fluidity assists easy cold start.
- Active cleaning agents provide superior engine cleanliness

**STREAM POWER OTB 4T** is recommended for:

- Outboard Motors: Honda, Mercury, Yamaha, Johnson/Evinrude, Bombardier/BRP, Suzuki, Nissan, Tohatsu.
- Inboard/Outboard Motors: Mercruiser, Volvo Penta, OMC, Chrysler Marine, Crusader, Marine Power, Chevrolet, Ford. • Personal Watercraft: Honda, Yamaha, Bombardier/BRP (Sea-Doo , Polaris).

**STREAM POWER OTB 4T** meets the following performance criteria:

NMMA-FC-W

### Typical Analysis

| Properties                  | Unit                   | Method           | Typical Value |
|-----------------------------|------------------------|------------------|---------------|
| SAE Grade                   |                        | SAE J300         | 10W-40        |
| Density @15°C               | kg/m <sup>3</sup>      | ASTM 4052        | 848           |
| Kinematic Viscosity @ 40°C  | mm <sup>2</sup> /s     | ASTM D7042       | 83.0          |
| Kinematic Viscosity @ 100°C | mm <sup>2</sup> /s     | ASTM D7042       | 13.40         |
| Viscosity Index             |                        | ASTM D2270       | 164           |
| Flash Point COC             | °C                     | ASTM D92         | 201           |
| Pour Point                  | °C                     | ASTM D7346       | -36           |
| Total Base Number           | mgKOH/g                | ASTM D2896       | 7.2           |
| Sulphated Ash               | %Wt                    | ASTM D874        | 0.8           |
| Date Issued: 16-6-2021      | Supersedes: 21-03-2016 | Revision Nr.: 01 |               |

